

## Closure Specifications

Closure Size (mm)	T		T1	E		E1	H	
	Min.	Max.	Max.	Min.	Max.	Max.	Min.	Max.
24-410	.941	.955	.964	.857	.871	.880	.622	.652
28-400	1.089	1.103	1.110	.995	1.009	1.016	.388	.406
28-410	1.089	1.103	1.112	.995	1.009	1.018	.684	.714
38-400	1.477	1.491	1.498	1.383	1.397	1.404	.388	.406
38-430	1.477	1.491	1.498	1.383	1.397	1.404	.941	.959
43-485	1.655	1.669	1.676	1.561	1.575	1.582	.406	.424
48-400	1.871	1.885	1.892	1.777	1.791	1.798	.388	.406
48-485	1.871	1.885	1.892	1.777	1.791	1.798	.406	.424
53-400	2.068	2.082	2.089	1.974	1.988	1.995	.388	.406
53-485	2.068	2.082	2.089	1.974	1.988	1.995	.401	.419
63-485	2.462	2.476	2.483	2.368	2.382	2.389	.401	.419
89-400	3.512	3.528	3.537	3.392	3.408	3.417	.515	.533
110-400	4.332	4.350	4.360	4.212	4.230	4.240	.577	.595

The "T" and "E" dimensions are to be measured at the top of the closure at a practical point near the end of a full thread.

The "T1" and "E1" Max. dimensions are to be measured near the bottom of the closure at the start of the full thread. The value for "T1" Max. and "E1" Max. include a draft angle.

*Closure specifications were taken from The Closure Manufacturers Association's (CMA) technical website.*